



Male Disconnects - Nylon Insulated with Insulation Grip




Product Number†	UPC (054007-)	Wire Range (AWG)	Male Tab Width(W) x Thickness	L	Barrel Length	Barrel I.D.	Maximum Insulation Diameter	Terminals per:	
								Carton	Case
MNG18-187DMK	02377	22-18	0.187 x 0.020	0.84	0.24	0.080	0.145	—	1000
MNG18-250DMX	02365	22-18	0.250 x 0.032	0.92	0.25	0.065	0.145	100	500
MNG18-250DMK	02378	22-18	0.250 x 0.032	0.92	0.25	0.065	0.145	—	1000
MNG14-187DMX	23003	16-14	0.187 x 0.020	0.84	0.24	0.080	0.145	100	500
MNG14-187DMK	01787	16-14	0.187 x 0.020	0.84	0.24	0.080	0.145	—	1000
MNG14-250DMX	23011	16-14	0.250 x 0.032	0.94	0.25	0.085	0.170	100	500
MNG14-250DMK	01788	16-14	0.250 x 0.032	0.94	0.25	0.085	0.170	—	1000
MNG10-250DMX	23938	12-10	0.250 x 0.032	1.05	0.25	0.150	0.250	50	500
MNG10-250DMK	02058	12-10	0.250 x 0.032	1.05	0.25	0.150	0.250	—	500




MNG18-187DM
22-18
Suggested Mate
MNG18-187DF




MNG18-250DM
22-18
Suggested Mate
MNG18-250DF



MNG14-187DM
16-14
Suggested Mate
MNG14-187DF



MNG14-250DM
16-14
Suggested Mate
MNG14-250DF



MNG10-250DM
12-10
Suggested Mate
MNG10-250DF

Wire Range
Suggested Mate