

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

Page 1 of 2

IDENTITY (As used on label and list)
Master Appliance Ultratane Butane Fuel

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

SECTION I.

MANUFACTURER'S NAME	Master Appliance Corp.	EMERGENCY TELEPHONE NO.	1-800-535-5053 (Infotrac)
ADDRESS	2420 18 TH Street	TELEPHONE NO. FOR INFORMATION	1-262-633-7791
	PO BOX 68	DATE PREPARED	January 6, 2011
	RACINE WI 53401	SIGNATURE OF PREPARER	(optional)

SECTION II. HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS

(Specific Chemical Identity: Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended % (optional)
Isobutane (CAS 75-28-5)	NE	800ppm	
Propane (CAS 74-98-6)	1000ppm	NE	
Butane (CAS 106-97-8)	800ppm	800ppm	

SECTION III. SHIPPING INFORMATION

PROPER SHIPPING NAME	Petroleum Gases, Liquefied
CLASS AND DIVISION NUMBER	2.1 (Flammable Gas)
UN NUMBER	UN-1075
REQUIRED LABELS	Flammable Gas label on each non-bulk package
PACKING GROUP	Not Listed

SECTION IV. PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT	11°F	SPECIFIC GRAVITY (H₂O = 1)	.571
VAPOR PRESSURE @70°F (psig)	30 ± 2	MELTING POINT	-138c
VAPOR DENSITY (air = 1)	1	EVAPORATION RATE (Butyl Acetate = 1)	1
SOLUBILITY IN WATER	Negligible		
APPEARANCE AND ODOR	Clear gas with light ethereal odor		

SECTION V. FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE LIMITS	LEL: 1.4 UEL: 9.5
FLASH POINT (METHOD USED)	-100°F Estimated
EXTINGUISHING MEDIA	Dry chemical, foam, carbon dioxide
SPECIAL FIRE FIGHTING PROCEDURES	Use water spray to cool containers. Avoid rocketing containers.
UNUSUAL FIRE AND EXPLOSION HAZARDS	Containers generate pressure when heated causing violent bursting and dangerous propelling of containers.

Material Safety Data Sheet For Master Appliance Ultratane Butane Fuel

January 6, 2011

Page 2 of 2

SECTION VI. REACTIVITY DATA

STABILITY	Stable: Yes Unstable:
CONDITIONS TO AVOID	Not established
INCOMPATIBILITY (Materials to Avoid)	Oxygen and strong oxidizing materials
HAZARDOUS DECOMPOSITION OR BYPRODUCTS	Carbon oxides formed when burned
HAZARDOUS POLYMERIZATION	May occur: Will not occur: Yes
CONDITIONS TO AVOID	Not established

SECTION VII. HEALTH HAZARD DATA

ROUTE(S) OF ENTRY	Inhalation? Yes (A)	Skin? Yes (B)	Ingestion? N/A
HEALTH HAZARDS (Acute and Chronic)	(A) Simple asphyxiant, dizziness, disorientation, headache, excitation, central nervous system depression, anesthesia. (B) Liquid contact with exposed skin can cause frostbite.		
CARCINOGENICITY? N/A	NTP? N/A	IARC MONOGRAPHS? N/A	OSHA REGULATED? N/A
SIGNS AND SYMPTOMS OF EXPOSURE	Dizziness, headache, ect.		
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE	None		
EMERGENCY AND FIRST AID PROCEDURES	Remove from exposure. If irritation develops seek medical attention.		

SECTION VIII. PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED	Protect from ignition. Ventilate area thoroughly.
WASTE DISPOSAL METHOD	Treatment, storage, transportation and disposal must be in accordance with applicable Federal, State and Local regulations.
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING	Store below 120°F. In case of accidental puncturing with forklift, shut off forklift and any other possible source of ignition. Ventilate area.
OTHER PRECAUTIONS	Use with adequate ventilation.

SECTION IX. CONTROL MEASURES

RESPIRATORY PROTECTION (Specific Type)	N/A
VENTILATION	Adequate
LOCAL EXHAUST	For small enclosed work areas
MECHANICAL (General)	Adequate for storage
PROTECTIVE GLOVES	Not required for normal handling
EYE PROTECTION	Safety Glasses
OTHER PROTECTIVE CLOTHING OR EQUIPMENT	Not required for normal handling
WORK/HYGIENIC PRACTICES	N/A

SECTION X. NFPA HAZARD CODES – HMIS RATING

HEALTH: 1 FIRE: 4 REACTIVITY: 0